



# Readyprint Markers

Readyprint heat-shrink markers are designed to meet the wire identification needs of commercial and industrial applications. They are UL and CSA approved and are fully compatible with the System Six range of printers and WinTotal software. Immediately after printing they are smudge resistant and permanent after shrinking. Readyprint markers have a 3:1 shrink-ratio and cover a wide range of diameters. Readyprint markers are a quick, easy and economical solution to a wide range of wire identification requirements.



## Technical Characteristics

Continuous operating temperature	-30°C to +105°C
Shrink ratio	3:1 (excluding 38mm = 2:1)
Printing options	Dot matrix & thermal transfer

## Part Numbering Information

Part No	Supplied Inside Diameter (mm)	Recovered Inside Diameter (mm)	Sleeve Length (mm)
RPS-22-18 - Colour	3.2	1.1	50
RPS-18-12 - Colour	4.8	1.6	50
RPS-16-10 - Colour	6.4	2.1	50
RPS-8-4 - Colour	9.5	3.2	50
RPS-10-2 - Colour	12.7	4.2	50
RPS-6-250 - Colour	19.1	6.4	50
RPS-1-400 - Colour	25.4	8.5	50
RPS-400-1000 - Colour	38.1	19.1	50

## Availability

Standard colours: Yellow (4) and White (9)  
 Pack sizes: 250, 1000 (1K) and 5000 (5K)

Specifications: UL E35586  
 CSA 31929

**Note:** For marked product add (M) to part number i.e. RPS-22-18-4(M)  
 For pre-scored product add S1, S2 or S3 to part number i.e. RPS-22-18-S1-4 for 1 score

## FULL PRINTING AND KITTING SERVICE AVAILABLE

